

Information requirements for electric local space heaters

Model identifier(s):

| Item | Symbol | Value | Unit | Item | Unit |
|--|--|-------|------|---|------|
| Heat output | | | | Type of heat input, for electric storage local space heaters only (select one) | |
| Nominal heat output | P_{nom} | | kW | manual heat charge control, with integrated thermostat | |
| Minimum heat output (indicative) | P_{min} | | kW | manual heat charge control with room and/or outdoor temperature feedback | |
| Maximum continuous heat output | $P_{max,c}$ | | kW | electronic heat charge control with room and/or outdoor temperature feedback | |
| Auxiliary electricity consumption | | | | fan assisted heat output | |
| At nominal heat output | el_{max} | | kW | Type of heat output/room temperature control (select one) | |
| At minimum heat output | el_{min} | | kW | single stage heat output and no room temperature control | |
| In standby mode | el_{SB} | | kW | Two or more manual stages, no room temperature control | |
| | | | | with mechanic thermostat room temperature control | |
| | | | | with electronic room temperature control | |
| | | | | electronic room temperature control plus day timer | |
| | | | | electronic room temperature control plus week timer | |
| | | | | Other control options (multiple selections possible) | |
| | | | | room temperature control, with presence detection | |
| | | | | room temperature control, with open window detection | |
| | | | | with distance control option | |
| | | | | with adaptive start control | |
| | | | | with working time limitation | |
| | | | | with black bulb sensor | |
| Contact details | Trotec GmbH · Grebbener Str. 7 · 52525 Heinsberg · Germany | | | | |